



New Jersey Department of Health and Senior Services

## HAZARDOUS SUBSTANCE FACT SHEET

Common Name: **METHYL ISOBUTYL  
KETONE**

CAS Number: 108-10-1  
DOT Number: UN 1245  
DOT Hazard Class: 3 (Flammable Liquid)

RTK Substance number: 1268  
Date: May 1998 Revision: August 2005

### HAZARD SUMMARY

- \* **Methyl Isobutyl Ketone** can affect you when breathed in.
- \* Contact can irritate and burn the eyes.
- \* Breathing **Methyl Isobutyl Ketone** can irritate the nose and throat causing coughing and wheezing.
- \* Breathing the vapor can cause headache, loss of appetite, nausea, vomiting, and diarrhea.
- \* Exposure to high concentrations can cause you to feel dizzy and lightheaded, and to pass out.
- \* Prolonged contact can cause a skin rash, dryness and redness.
- \* **Methyl Isobutyl Ketone** may damage the liver and kidneys.
- \* **Methyl Isobutyl Ketone** is a **FLAMMABLE LIQUID** and a **FIRE HAZARD**.

### IDENTIFICATION

**Methyl Isobutyl Ketone** is a colorless liquid with a pleasant odor. It is used as a solvent.

### REASON FOR CITATION

- \* **Methyl Isobutyl Ketone** is on the Hazardous Substance List because it is regulated by OSHA and cited by ACGIH, DOT, NIOSH, DEP, IRIS, NFPA and EPA.
- \* This chemical is on the Special Health Hazard Substance List because it is **FLAMMABLE**.
- \* Definitions are provided on page 5.

### HOW TO DETERMINE IF YOU ARE BEING EXPOSED

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

- \* Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.1020.
- \* If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.
- \* **ODOR THRESHOLD = 0.88 ppm.**
- \* The range of accepted odor threshold values is quite broad. Caution should be used in relying on odor alone as a warning of potentially hazardous exposures.

### WORKPLACE EXPOSURE LIMITS

- OSHA: The legal airborne permissible exposure limit (PEL) is **100 ppm** averaged over an 8-hour workshift.
- NIOSH: The recommended airborne exposure limit is **50 ppm** averaged over a 10-hour workshift and **75 ppm**, not to be exceeded during any 15-minute work period.
- ACGIH: The recommended airborne exposure limit is **50 ppm** averaged over an 8-hour workshift and **75 ppm** as a STEL (short term exposure limit).

### WAYS OF REDUCING EXPOSURE

- \* Where possible, enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- \* Wear protective work clothing.
- \* Wash thoroughly immediately after exposure to **Methyl Isobutyl Ketone** and at the end of the workshift.
- \* Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of **Methyl Isobutyl Ketone** to potentially exposed workers.

This Fact Sheet is a summary source of information of all potential and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

---

## HEALTH HAZARD INFORMATION

### Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Methyl Isobutyl Ketone**:

- \* Contact can irritate and burn the eyes.
- \* Breathing **Methyl Isobutyl Ketone** can irritate the nose and throat causing coughing and wheezing.
- \* Breathing the vapor can cause headache, loss of appetite, nausea, vomiting, and diarrhea.
- \* Exposure to high concentrations can cause you to feel dizzy and lightheaded, and to pass out.

### Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Methyl Isobutyl Ketone** and can last for months or years:

### Cancer Hazard

- \* According to the information presently available to the New Jersey Department of Health and Senior Services, **Methyl Isobutyl Ketone** has not been tested for its ability to cause cancer in animals.

### Reproductive Hazard

- \* According to the information presently available to the New Jersey Department of Health and Senior Services, **Methyl Isobutyl Ketone** has been tested and has not been shown to affect reproduction.

### Other Long-Term Effects

- \* Prolonged contact can cause a skin rash, dryness and redness.
- \* **Methyl Isobutyl Ketone** may damage the liver and kidneys.

## MEDICAL

### Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- \* Liver and kidney function tests.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.1020.

### Mixed Exposures

- \* Because more than light alcohol consumption can cause liver damage, drinking alcohol can increase the liver damage caused by **Methyl Isobutyl Ketone**.

## WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following controls are recommended:

- \* Where possible, automatically pump liquid **Methyl Isobutyl Ketone** from drums or other storage containers to process containers.
- \* Before entering a confined space where **Methyl Isobutyl Ketone** may be present, check to make sure that an explosive concentration does not exist.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

- \* Workers whose clothing has been contaminated by **Methyl Isobutyl Ketone** should change into clean clothing promptly.
- \* Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **Methyl Isobutyl Ketone**.
- \* Eye wash fountains should be provided in the immediate work area for emergency use.
- \* If there is the possibility of skin exposure, emergency shower facilities should be provided.
- \* On skin contact with **Methyl Isobutyl Ketone**, immediately wash or shower to remove the chemical. At the end of the workshift, wash any areas of the body that may have contacted **Methyl Isobutyl Ketone**, whether or not known skin contact has occurred.
- \* Do not eat, smoke, or drink where **Methyl Isobutyl Ketone** is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating, drinking, smoking, or using the toilet.

## PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

### Clothing

- \* Avoid skin contact with **Methyl Isobutyl Ketone**. Wear solvent-resistant gloves and clothing. Safety equipment suppliers/ manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- \* Safety equipment manufacturers recommend *Butyl Neoprene rubber, 4H®*; and *Polyvinyl Alcohol* as protective materials.
- \* All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

### Eye Protection

- \* Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- \* Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- \* Contact lenses should not be worn when working with this substance.

### Respiratory Protection

**IMPROPER USE OF RESPIRATORS IS DANGEROUS.** Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- \* Where the potential exists for exposure over **50 ppm**, use a MSHA/NIOSH approved full facepiece respirator with an organic vapor cartridge. Increased protection is obtained from full facepiece powered-air purifying respirators.
- \* If while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Methyl Isobutyl Ketone**, or if while wearing particulate filters abnormal resistance to breathing is experienced, or eye irritation occurs while wearing a full facepiece respirator, leave the area immediately. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.

- \* Be sure to consider all potential exposures in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- \* Where the potential for high exposure exists, use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.
- \* Exposure to **500 ppm** is immediately dangerous to life and health. If the possibility of exposure above **500 ppm** exists, use a NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode equipped with an emergency escape air cylinder.

## HANDLING AND STORAGE

- \* Prior to working with **Methyl Isobutyl Ketone** you should be trained on its proper handling and storage.
- \* **Methyl Isobutyl Ketone** may form explosive *Peroxides* with exposure to AIR.
- \* **Methyl Isobutyl Ketone** is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); AMINES; POTASSIUM tert-BUTOXIDE; ALDEHYDES; and REDUCING AGENTS.
- \* Store in tightly closed containers in a cool, well-ventilated area away from HEAT, SPARKS and FLAMES.
- \* Sources of ignition, such as smoking and open flames, are prohibited where **Methyl Isobutyl Ketone** is used, handled, or stored.
- \* Metal containers involving the transfer of **Methyl Isobutyl Ketone** should be grounded and bonded.
- \* Use only non-sparking tools and equipment, especially when opening and closing containers of **Methyl Isobutyl Ketone**.

## QUESTIONS AND ANSWERS

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.
- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.

- Q: What are my chances of getting sick when I have been exposed to chemicals?
- A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.
- Q: When are higher exposures more likely?
- A: Conditions which increase risk of exposure include physical and mechanical processes (heating, pouring, spraying, spills and evaporation from large surface areas such as open containers), and "confined space" exposures (working inside vats, reactors, boilers, small rooms, etc.).
- Q: Is the risk of getting sick higher for workers than for community residents?
- A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. This may be a problem for children or people who are already ill.

---

The following information is available from:

New Jersey Department of Health and Senior Services  
Occupational Health Service  
PO Box 360  
Trenton, NJ 08625-0360  
(609) 984-1863  
(609) 984-7407 (fax)

Web address: <http://www.state.nj.us/health/eoh/odisweb/>

### **Industrial Hygiene Information**

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

### **Medical Evaluation**

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call personnel at the Department of Health and Senior Services, Occupational Health Service, who can help you find the information you need.

### **Public Presentations**

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

### **Right to Know Information Resources**

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know Survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

---

## DEFINITIONS

**ACGIH** is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

**CFR** is the Code of Federal Regulations, which consists of the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

**DEP** is the New Jersey Department of Environmental Protection.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

**IARC** is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

**IRIS** is the Integrated Risk Information System database of the federal EPA.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

**mg/m<sup>3</sup>** means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

**NAERG** is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

**NFPA** is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

**OSHA** is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEL** is the Permissible Exposure Limit which is enforceable by the Occupational Safety and Health Administration.

**PIH** is a DOT designation for chemicals which are Poison Inhalation Hazards.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

**STEL** is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**TLV** is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

CHEMTREC: (800) 424-9300  
NJDEP HOTLINE: 1-877-WARN-DEP

|   |        |      |
|---|--------|------|
| Hazard rating   | NJDHSS | NFPA |
| <b>FLAMMABILITY</b>   | -      | 3    |
| <b>REACTIVITY</b>   | -      | 1    |
| FLAMMABLE<br>POISONOUS GASES ARE PRODUCED IN FIRE<br>CONTAINERS MAY EXPLODE IN FIRE |        |      |

*Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe*

## FIRE HAZARDS

- \* **Methyl Isobutyl Ketone** is a FLAMMABLE LIQUID.
- \* Use dry chemical, CO<sub>2</sub>, alcohol-resistant foam or other foaming agent, as water may not be effective in fighting fires.
- \* **POISONOUS GASES ARE PRODUCED IN FIRE.**
- \* **CONTAINERS MAY EXPLODE IN FIRE.**
- \* Use water spray to keep fire-exposed containers cool.
- \* Vapors may travel to a source of ignition and flash back.
- \* Vapor is heavier than air and may travel a distance to cause a fire or explosion far from the source.
- \* If employees are expected to fight fires, they must be trained and equipped as stated in OSHA 1910.156.

## SPILLS AND EMERGENCIES

If **Methyl Isobutyl Ketone** is spilled or leaked, take the following steps:

- \* Evacuate persons not wearing protective equipment from area of spill or leak until clean-up is complete.
- \* Remove all ignition sources.
- \* Cover with an activated charcoal adsorbent and place in covered containers for disposal.
- \* Ventilate and wash area after clean-up is complete.
- \* Keep **Methyl Isobutyl Ketone** out of a confined space, such as a sewer, because of the possibility of an explosion, unless the sewer is designed to prevent the build-up of explosive concentrations.
- \* It may be necessary to contain and dispose of **Methyl Isobutyl Ketone** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.
- \* If employees are required to clean-up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

## HANDLING AND STORAGE (See page 3)

## FIRST AID

**For POISON INFORMATION call 1-800-222-1222**

## Eye Contact

- \* Immediately flush with large amounts of water for at least 15 minutes, occasionally lifting upper and lower lids. Seek medical attention immediately.

## Skin Contact

- \* Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water.

## Breathing

- \* Remove the person from exposure.
- \* Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- \* Transfer promptly to a medical facility.

## PHYSICAL DATA

**Vapor Pressure:** 16 mm Hg at 68°F (20°C)

**Flash Point:** 64°F (18°C)

**Water Solubility:** Soluble

## OTHER COMMONLY USED NAMES

**Chemical Name:**

2-Pentanone, 4-Methyl-

**Other Names:**

MIBK; Hexone; Isopropylacetone

*Not intended to be copied and sold for commercial purposes.*

NEW JERSEY DEPARTMENT OF HEALTH AND  
SENIOR SERVICES

## Right to Know Program

PO Box 368, Trenton, NJ 08625-0368  
(609) 984-2202